

class 800 dişli / soket kaynaklı küresel vanalar (1600-1650)

class 800 threaded / socket weld ball valves (1600-1650)

- DN15-DN50,
- Basınç Sınıfı : Class 800,
- Gövde & Kapak : ASTM A-105 / AISI 316,
- Küre : ASTM A-105 / AISI 316,
- Kumanda Şekli : Kollu,
- ASME B16,11 / ASME B1.20.1 standartlarına uygun.

- DN15-DN50,
- Pressure Class : Class 800,
- Body & Cap : ASTM A-105 / AISI 316,
- Ball : ASTM A-105 / AISI 316,
- Operation : Lever,
- According to ASME B16,11 / ASME B1.20.1 standards.



PN 63 iki / üç parçalı dişli küresel vanalar (1700-1750)

PN 63 two / three piece threaded ball valves (1700-1750)

Burçelik PN 63 dişli küresel vanalar, tam geçişli, 2 ve 3 parçalı olarak üretilmektedir. Bu vanalar 1000 psi / 68 bar basınca dayanıklıdır.

- DN15-DN50,
- Basınç Sınıfı : PN63,
- Gövde & Kapak : ASTM A-105 / AISI 316,
- Küre : ASTM A-105 / AISI 316,
- Kumanda Şekli : Kollu,
- TS EN 331 standartına uygun.

Burçelik PN 63 threaded ball valves manufactured with full bore, 2 and 3 piece threaded. These ball valves can be resistant up to 1000 psi / 68 bar pressure.

- DN15-DN50,
- Pressure Class : PN63,
- Body & Cap : ASTM A-105 / AISI 316,
- Ball : ASTM A-105 / AISI 316,
- Operation : Lever,
- According to TS EN 331 standard.

